



N100 PORT SYSTEM FOR NIKON Z-MOUNT CAMERA SYSTEM  
( DX & F-Mount Format Lens )

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO DX	NIKKOR Z MC 50mm f/2.8 Macro			37401 N100 Extension Ring 30	37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification Working Distance	1.3X 8-66mm
							81302 CMC - 2	Max. Magnification Working Distance	1.2X 4-120mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification Working Distance	1.3X 8-66mm
							81302 CMC - 2	Max. Magnification Working Distance	1.2X 4-120mm
					37124 Flat port 66 with M77 Thread	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV Converted FOV	31.5° 119°
						SMC/CMC Option 1 - Bayonet Mount 83251 + 83214 M77 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification Working Distance	1.3X 8-66mm
							81302 CMC - 2	Max. Magnification Working Distance	1.2X 4-120mm
						83251 M77 to Bayonet Mount Converter II	86201 MWL - 1	Lens FOV Converted FOV	31.5° 119°
STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR	37602 Z1650PZ-Z			37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification Working Distance	0.9X 45.5-75mm
							81302 CMC - 2	Max. Magnification Working Distance	0.67X 70-130mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification Working Distance	0.9X 45.5-75mm
							81302 CMC - 2	Max. Magnification Working Distance	0.67X 70-130mm
						83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84-31.5° 130-49°
							<sup>1</sup> 83201 WWL-1	Lens FOV Converted FOV Zoom Range	72-31.5° 125-55° 20-50mm
							83202 WWL-1B	Lens FOV Converted FOV Zoom Range	72-31.5° 125-55° 20-50mm
NIKON F-MOUNT	Nikon F-mount Lenses with Nikon Adaptor FTZ  <i>* It is required to replace tripod socket cover of Nikon adaptor FTZ by #25220 Tripod socket replacement</i>		37305 N100 to N120 35.5mm Port Adaptor II		N120 Nikon F-Mount Port System				

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance

\* Secondary setup recommendation based on optical performance