



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO FOUR THIRDS	Olympus M.Zuiko Digital ED 30mm f3.5 Macro				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV Converted FOV	39° 150°
	Olympus M.Zuiko Digital ED 60mm f2.8 Macro	36149 O60-F			36163 N85 Macro Port 65	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification Working Distance	2.0X 22-70mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification Working Distance	1.7X 33-122mm
						83250 M67 to Bayonet Mount Converter II	81301 CMC - 1	Max. Magnification Working Distance	2.0X 22-70mm
						81302 CMC - 2	81302 CMC - 2	Max. Magnification Working Distance	1.7X 33-122mm
						83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV Converted FOV	20° 60°/100°/130°
				36620 N85 Extension Ring 20	36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification Working Distance	2.0X 22-70mm
						81302 CMC - 2	81302 CMC - 2	Max. Magnification Working Distance	1.7X 33-122mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification Working Distance	2.0X 22-70mm
						81302 CMC - 2	81302 CMC - 2	Max. Magnification Working Distance	1.7X 33-122mm
	Panasonic Lumix G Macro 30mm f/2.8 Asph. Mega O.I.S.				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV Converted FOV	39° 150°
	Panasonic LEICA DG MACRO-ELMARIT 45mm F2.8 ASPH. MEGA O.I.S.	36145 P45-F			36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification Working Distance	1.6X 17-73mm
						81302 CMC - 2	81302 CMC - 2	Max. Magnification Working Distance	1.4X 23-124mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification Working Distance	1.6X 17-73mm
						81302 CMC - 2	81302 CMC - 2	Max. Magnification Working Distance	1.4X 23-124mm
						83250 M67 to Bayonet Mount Converter II	87303 EMWL Set #3	Lens FOV Converted FOV	20° 60°/100°/130°
	Laowa 24mm f/14 2X Macro Probe <i>* with Metabones T Speed Booster Ultra 0.71X Adapter on NA-GH5 housing</i>	19155 N120 DSLR Gear Set	36064 N85 to N120 34.7mm Port Adaptor	21271 Extension Ring 70 with Focus Knob	16336 N120 Port Adaptor for Laowa 24mm f/14 2X Macro Probe				

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
STANDARD ZOOM FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO	36045 O1240-Z	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36129 N85 7" Acrylic Dome Port			Lens FOV	75-45°
					* 85201 WACP - 1			Converted FOV	130-57°
		36045 + 36065 O1240-Z + O1240-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>		* 18809 180mm Optical Glass Wide Angle Port			Zoom Range	14-32mm
					85201 WACP - 1			Lens FOV	75-45°
	Olympus M.ZUIKO DIGITAL ED 12-45mm f/4 PRO	36069 O1245-Z		36620 +36620 N85 Extension Ring 20 + 20	36129 N85 7" Acrylic Dome Port			Converted FOV	130-68°
					18809 180mm Optical Glass Wide Angle Port			Zoom Range	14-26mm
					36139 N85 Macro Port 35	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification	0.7X
							81302 CMC - 2	Working Distance	24-74mm
		36069 + 36070 O1240-Z + O1240-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>			SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification	0.5X
							81302 CMC - 2	Working Distance	39-130mm
					* 18809 180mm Optical Glass Wide Angle Port			Max. Magnification	0.7X
								Working Distance	24-74mm
	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36064 N85 to N120 34.7mm Port Adaptor			85201 WACP - 1			Max. Magnification	0.5X
					* this setup is not compatible with NA-EM1X			Working Distance	39-130mm
		36069 + 36070 O1240-Z + O1240-F	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>					Lens FOV	75-45°
					18809 180mm Optical Glass Wide Angle Port			Converted FOV	130-58°
	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 & NA-EM1X</i>			36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Zoom Range	14-29mm
							81302 CMC - 2	Max. Magnification	0.8X
								Working Distance	40-70mm
					36161 N85 Macro Port with M77 Thread	83251 M77 to Bayonet Mount Converter II	86201 MWL - 1	Max. Magnification	0.6X
	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ						83203 WWL-C	Working Distance	70-120mm
								Lens FOV	39-34°
								Converted FOV	150-71°
								Zoom Range	30-50mm
	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ							Lens FOV	72-24°
								Converted FOV	110-37°
								Zoom Range	14-50mm

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM FOUR THIRDS	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 & NA-EM1X</i>	36161 N85 Macro Port with M77 Thread	83251 + 83214 M77 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 14-61mm
					81302 CMC - 2	Max. Magnification 0.7X Working Distance 24-95mm
	Olympus M.Zuiko Digital 14-42mm f/3.5-6.3 II R	36143 O1442-Z	36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm
			36136 N85 Macro Port 56	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm
				SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm
				83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°
					83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50°
		36143 + 36067 O1442-Z + O1442-F	36166 N85 Macro Port 56 with Focus Knob	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50° <i>* zoom range for BMPCC II</i>
					83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50° <i>* zoom range for BMPCC II</i>
	Olympus M.Zuiko Digital 14-42mm f/3.5-5.6 EZ	36047 O1442EZ-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1	Lens FOV 75-29° Converted FOV 130-50°
					83202 WWL - 1B	Lens FOV 75-29° Converted FOV 130-50°
				SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm
				SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 41-76mm
					81302 CMC - 2	Max. Magnification 0.6X Working Distance 63-130mm

¹. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

** Recommended port system based on best optical performance*

** Secondary setup recommendation based on optical performance*



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM FOUR THIRDS	Panasonic LUMIX G VARIO 12-32mm F3.5-5.6 ASPH. ASPH. MEGA O.I.S.	36046 P1232-Z		36620 N85 Extension Ring 20	36131 N85 3.5" Acrylic Wide Angle Port			
					36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV Converted FOV Zoom Range75-37° 130-64° 13-32mm
							83202 WWL - 1B	Lens FOV Converted FOV Zoom Range75-37° 130-64° 13-32mm
							83203 WWL-C	Lens FOV Converted FOV84-37° 130-57°
	Panasonic LUMIX G X Vario 12-35mm F2.8 I/ II ASPH. POWER O.I.S.	36148 P1235-Z			36133 N85 6" Acrylic Wide Angle Port			
			36064 N85 to N120 34.7mm Port Adaptor		* 85201 WACP - 1 <i>* this setup is not compatible with NA-EM1X</i>			Lens FOV Converted FOV Zoom Range75-52° 130-90° 14-22mm
		36148 + 36042 P1235-Z + P1235-F			36164 N85 6" Acrylic Wide Angle Port with Focus Knob			
			36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	85201 WACP - 1			Lens FOV Converted FOV Zoom Range75-40° 130-69° 14-30mm
	Panasonic LEICA DG VARIO-ELMARIT 12-60mm F2.8-4.0 ASPH. POWER O.I.S.	36058 PL1260-Z			36129 N85 7" Acrylic Dome Port			
		36058 + 36068 PL1260-Z + PL1260-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>		* 18809 180mm Optical Glass Wide Angle Port			
	Panasonic LUMIX G 14mm / F2.5 ASPH				36131 N85 3.5" Acrylic Wide Angle Port			
					36151 N85 Pancake Port	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV Converted FOV75° 130°
							83202 WWL - 1B	Lens FOV Converted FOV75° 130°
	Panasonic LUMIX G Vario 14-42mm F3.5-5.6 ASPH. MEGA O.I.S.	36141 P1442-Z			36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification Working Distance0.7X 50-70mm
							81302 CMC - 2	Max. Magnification Working Distance0.6X 80-120mm
					36121 N85 Flat Port 72	25104 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1	Max. Magnification Working Distance0.7X 50-70mm
							81302 CMC - 2	Max. Magnification Working Distance0.6X 80-120mm

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE		
STANDARD ZOOM FOUR THIRDS	Panasonic LUMIX G Vario 14-42mm F3.5-5.6 II ASPH. MEGA O.I.S.	36057 P1442II-Z			36139 N85 Flat Port 35	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1		Max. Magnification	0.7X
									Working Distance	49-72mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2		Max. Magnification	0.6X
									Working Distance	77-122mm
							81301 CMC - 1		Max. Magnification	0.7X
									Working Distance	50-70mm
		81302 CMC - 2		Max. Magnification	0.6X					
				Working Distance	80-120mm					
	Panasonic LUMIX G Vario PZ 14-42mm F3.5-5.6 ASPH. POWER O.I.S.	36146 P1442X-PZ <i>* 36061 P1442X-PZ for NA-GH5</i>			36165 N85 Power Zoom Macro Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1		Max. Magnification	0.7X
									Working Distance	49-72mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2		Max. Magnification	0.6X
									Working Distance	77-122mm
						81301 CMC - 1		Max. Magnification	0.7X	
								Working Distance	50-70mm	
	81302 CMC - 2		Max. Magnification	0.6X						
			Working Distance	80-120mm						
Panasonic LUMIX G Vario 14-45mm F3.5-5.6 ASPH. MEGA O.I.S.	36053 P1445-Z			36137 N85 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder + M67 Adaptor Ring	81301 CMC - 1		Max. Magnification	0.8X	
								Working Distance	40-75mm	
					81302 CMC - 2		Max. Magnification	0.6X		
							Working Distance	60-130mm		
					81301 CMC - 1		Max. Magnification	0.8X		
							Working Distance	40-75mm		
	81302 CMC - 2		Max. Magnification	0.6X						
			Working Distance	60-130mm						
WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO	36054 + 36055 O714-Z + O714-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>		18809 180mm Optical Glass Wide Angle Port					
	Olympus M.ZUIKO DIGITAL ED 8-25mm f4 PRO	36071 O825-Z	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21140 Extension Ring 40 with Lock	18809 180mm Optical Glass Wide Angle Port					
	<i>* Please refer to the following page for more setup options</i>			21120 Extension Ring 20 with Lock	<i>★ 85201 WACP - 1</i>				Lens FOV Converted FOV Zoom Range	75-47° 130-81° 14-25mm



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 8-25mm f4 PRO	36071 0825-Z	36064 N85 to N120 34.7mm Port Adaptor	21160 Extension Ring 60 with Lock 21140 Extension Ring 40 with Lock	18809 180mm Optical Glass Wide Angle Port * 85201 WACP - 1 <i>* this setup is not compatible with NA-EM1X</i>	Lens FOV	75-47°
	Olympus M.ZUIKO DIGITAL ED 9-18mm f/4-5.6	36143 0918-Z	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i> 36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36137 N85 4" Acrylic Wide Angle Port * 18809 180mm Optical Glass Wide Angle Port	Converted FOV	130-81°
	Olympus M.ZUIKO DIGITAL ED 12mm f/2.0			36620 N85 Extension Ring 20	36132 N85 4.33" Acrylic Fisheye Dome Port <i>* this setup is not compatible with NA-EM1X</i> * 36048 N85 140mm Optical Glass Fisheye Port 36131 N85 3.5" Acrylic Wide Angle Port	Zoom Range	14-25mm
	Panasonic LUMIX G Vario 7-14mm F4.0 ASPH.	36044 P714-Z 36044 + 36043 P714-Z + P714-F	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SN297188 onwards for NA-EM1X</i>		36133 N85 6" Acrylic Wide Angle Port 36164 N85 6" Acrylic Wide Angle Port with Focus Knob * 18809 180mm Optical Glass Wide Angle Port		
	Panasonic LEICA DG VARIO-ELMARIT 8-18mm F2.8-4.0 ASPH.	36062 PL818-Z 36062 + 36063 PL818-Z + PL818-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SN393297 onwards for NA-EM1X</i>	21120 Extension Ring 20 with Lock	36129 N85 7" Acrylic Dome Port * 18809 180mm Optical Glass Wide Angle Port		
FISHEYE FOUR THIRDS	Olympus M.Zuiko Digital ED 8mm f/1.8 Fisheye PRO	36056 08-F		36617 N85 Extension Ring 17 36620 N85 Extension Ring 20	* 36048 N85 140mm Optical Glass Fisheye Port 36132 N85 4.33" Acrylic Fisheye Dome Port		

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 MICRO FOUR THIRDS SYSTEM FOR MICRO FOUR THIRD CAMERA SYSTEMS

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT
FISHEYE FOUR THIRDS	Panasonic LUMIX G FISHEYE 8mm F3.5	36041 P8-F			* 36048 N85 140mm Optical Glass Fisheye Port
					36131 N85 3.5" Acrylic Wide Angle Port <i>* this setup is not compatible with NA-EM1X</i>
					36132 N85 4.33" Acrylic Fisheye Dome Port
	Panasonic LUMIX G Vario PZ 14-42mm F3.5-5.6 ASPH. MEGA O.I.S. with Panasonic LUMIX G Vario DMW-GFC1 for G Series	36146 P1442X-PZ <i>* 36061 P1442X-PZ for NA-GH5</i>		36630 N85 Extension Ring 30	36132 N85 4.33" Acrylic Fisheye Dome Port
CANON EF-MOUNT	Canon EF-mount Lenses with Metabones T Speed Booster Ultra 0.71X Adapter		36064 N85 to N120 34.7mm Port Adaptor		N120 Canon EF-Mount Port System <i>* this setup is not compatible with NA-EM1X</i>

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance