



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE		
N120 CINEMA SYSTEM (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC)	WIDE ANGLE APSC	Canon EF-S 10-18mm f/4.5-5.6 IS STM	16340 RC1018 Gear Set		85204 WACP - 2	On APS-C Sensor	Lens FOV	108-75°
		Canon EF-S 10-22mm f/3.5-4.5 IS USM	16303 + 16304 RC1022-Z + RC1022-F	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 before SN:A526311</i>	On APS-C Sensor	Lens FOV	108-63°
				22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	On APS-C Sensor	Converted FOV	128-85°
		Tokina AT-X 11-20mm F2.8 PRO DX	16328 RTC1120 Gear Set	21120 Extension Ring 20 with Lock	85204 WACP - 2	On APS-C Sensor	Lens FOV	108-63°
		Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	16309 + 16310 RSC1116-Z + RSC1116-F	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 before SN:A526311</i>	On APS-C Sensor	Converted FOV	128-72°
	WIDE ANGLE FULL FRAME			22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	On APS-C Sensor	Lens FOV	108-63°
		Canon RF 14-35mm f/4L IS USM	16342 CR1435 Gear Set	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 before SN:A526311</i>	On APS-C Sensor	Lens FOV	100-68°
						On Full Frame Sensor	Converted FOV	118-78°
				22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	On APS-C Sensor	Lens FOV	110-81°
						On Full Frame Sensor	Converted FOV	118-92°
		Canon RF 15-35mm f/2.8L IS USM	16341 CR1535 Gear Set	21135 Extension Ring 35 with Lock	85204 WACP - 2	On APS-C Sensor	Lens FOV	110-81°
						On Full Frame Sensor	Converted FOV	118-92°
		Canon EF 16-35mm f/2.8 II USM	16311 + 16312 RC1635II-Z + RC1635II-F	21130 Extension Ring 30 with Lock	85204 WACP - 2	On APS-C Sensor	Lens FOV	89-42°
						On Full Frame Sensor	Converted FOV	104-48°
		Canon EF 16-35mm f/2.8 III USM	16325 RC1635III Gear Set	21150 Extension Ring 50 with Lock	85204 WACP - 2	On APS-C Sensor	Lens FOV	114-63°
						On Full Frame Sensor	Converted FOV	140-72°
		Canon EF 16-35mm f/4L IS USM	16317 + 16318 RC1635f4-Z + RC1635f4-F	21130 Extension Ring 30 with Lock	85204 WACP - 2	On APS-C Sensor	Lens FOV	89-42°
						On Full Frame Sensor	Converted FOV	104-48°
		Canon RF 28-70mm f2L USM	16343 RC2870f2 Gear Set	21140 Extension Ring 40 with Lock	85204 WACP - 2	On Full Frame Sensor	Lens FOV	84-42°
							Converted FOV	98-48°
							Zoom Range	110-63°
								128-72°
								75-63°
								85-72°
								28-35mm

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.
* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
N120 NIKON F-MOUNT	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z	21150 Extension Ring 50 with Lock	* 85204 WACP - 2	Lens FOV 105-63° Converted FOV 128-72°
		19138 + 19142 N1635-Z + N1635-F	21240 Extension Ring 40 with Focus Knob	85204 WACP - 2	Lens FOV 105-63° Converted FOV 128-72°
	Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z	21130 Extension Ring 30 with Lock	85204 WACP - 2	Lens FOV 104-63° Converted FOV 123-72°
		19130 + 19159 N1735-Z + N1735-F <i>* a spacer is required for this setup (incl. in package)</i>	21235 Extension Ring 30 with Focus Knob	* 85204 WACP - 2	Lens FOV 104-63° Converted FOV 123-72°
N120 NIKON Z-MOUNT	Nikkor Z 24-70mm f/2.8 S Lens	19157 NZ2470f2.8S-Z	21125 Extension Ring 25 with Lock	85204 WACP - 2	Lens FOV 84-46° Converted FOV 98-56° Zoom Range 24-50mm
	Nikkor Z 14-24mm f/2.8 S	19160 NZ1424-Z	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>	Lens FOV 114-87° Converted FOV 140-98°
			22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	Lens FOV 114-87° Converted FOV 140-98°
	Nikkor Z 14-30mm f/4 S	19156 NZ1430-Z		85204 WACP - 2	Lens FOV 114-72° Converted FOV 140-81°
N120 CANON EF-MOUNT	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19549 C1018-Z		85204 WACP - 2	Lens FOV 108-75° Converted FOV 128-85°
	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>	Lens FOV 108-63° Converted FOV 128-72°
			22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	Lens FOV 108-63° Converted FOV 128-72°
	Tokina AT-X 11-20mm F2.8 PRO DX	19573 CT1120-Z	21120 Extension Ring 20 with Lock	85204 WACP - 2	Lens FOV 104-72° Converted FOV 123-81°
	Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19530 TC1116-Z	21110 N120 Extension Ring 10	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>	Lens FOV 110-81° Converted FOV 133-92°
			22110 N120 Extension Ring 10 II	85204 WACP - 2 <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	Lens FOV 110-81° Converted FOV 133-92°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.
* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	EXTENSION RING	PORT		OPTICAL PERFORMANCE	
N120 CANON EF-MOUNT	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z	21130 Extension Ring 30 with Lock	* 85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°
			19527 + 19542 C1635II-Z + C1635II-F	21230 Extension Ring 30 with Focus Knob	85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°
		Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z	21150 Extension Ring 50 with Lock	* 85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°
			19554 + 19555 C1635III-Z + C1635III-F	21250 Extension Ring 50 with Focus Knob	85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°
		Canon EF 16-35mm f/4 IS USM	19548 C1635f4-Z	21130 Extension Ring 30 with Lock	* 85204 WACP - 2		Lens FOV Converted FOV	108-63° 128-72°
			19548 + 19572 C1635f4-Z + WC1635f4-F	21235 Extension Ring 35 with Focus Knob	85204 WACP - 2		Lens FOV Converted FOV	108-63° 128-72°
N120 CANON RF-MOUNT	WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21110 N120 Extension Ring 10	85204 WACP - 2	* This setup is only compatible with WACP-2 SN:A526311 before	Lens FOV Converted FOV	114-63° 140-72°
				22110 N120 Extension Ring 10 II	85204 WACP - 2	* This setup is only compatible with WACP-2 SN:A526311 onwards	Lens FOV Converted FOV	114-63° 140-72°
		Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z	21135 Extension Ring 35 with Lock	85204 WACP - 2		Lens FOV Converted FOV	110-63° 133-72°
			19569 + 19571 CR1535-Z + WCR1535-F	21235 Extension Ring 35 with Focus Knob	* 85204 WACP - 2		Lens FOV Converted FOV	110-63° 133-72°
	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f2.8L USM	19595 CR2870-Z	21140 Extension Ring 40 with Lock	85204 WACP - 2	* This setup is only compatible with WACP-2 SN:A526311 onwards	Lens FOV Converted FOV Zoom Range	75-63° 85-72° 28-35mm
	N120 PANASONIC	WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	19728 PL1635-Z		85204 WACP - 2		Lens FOV Converted FOV
Sigma 14-24mm F2.8 DG DN Art			19726 SLE1424-Z	21125 Extension Ring 25 with Lock	85204 WACP - 2		Lens FOV Converted FOV Zoom Range	94-84° 115-98° 20-24mm
N120 FUJIFILM G-MOUNT	MACRO MEDIUM FORMAT	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17-A + GL17-F	21235 Extension Ring 35 with Focus Knob	85204 WACP - 2		Lens FOV Converted FOV	114° 140°
	WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 23mm F4 R LM WR		21120 Extension Ring 20 with Lock	85204 WACP - 2		Lens FOV Converted FOV	100° 118°
		Canon EF 16-35mm f/2.8 III USM	TBD CGF1635III-Z	21180 Extension Ring 80 with Lock	85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°
		Canon EF 16-35mm f/4 IS USM	TBD CGF1635f4-Z	21160 Extension Ring 60 with Lock	85204 WACP - 2		Lens FOV Converted FOV	107-63° 128-72°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.
* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Sony SEL2470GM FE 24-70mm F2.8 GM	37151 SFE2470GM-Z 37151 + 37152 SFE2470GM-Z + SFE2470GM-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21130 Extension Ring 30 with Lock	85204 WACP - 2	Lens FOV Converted FOV Zoom Range84-34° 98-72° 24-35mm
	Sony SEL2470Z Vario-Tessar T* FE 24-70mm F4 ZA OSS	37149 SE2470-Z 37149 + 37148 SE2470-Z + SE2470-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 WACP - 2	Lens FOV Converted FOV Zoom Range84-34° 98-72° 24-35mm
	Sigma 24-70mm f/2.8 DG DN Art	37171 SSF2470-Z	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21120 Extension Ring 20 with Lock	85204 WACP - 2	Lens FOV Converted FOV Zoom Range84-64° 98-74° 24-34mm
N100 SONY E-MOUNT WIDE ANGLE FULL FRAME	Sony FE 14mm f/1.8 GM		37306 N100 to N120 25mm Port Adaptor		85204 WACP - 2	Lens FOV Converted FOV114° 140°
	Sony SEL1635GM FE 16-35mm F2.8 GM	37155 SFE1635GM-Z 37155 + 37156 SFE1635GM-Z + SFE1635GM-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21130 Extension Ring 30 with Lock	85204 WACP - 2	Lens FOV Converted FOV107-63° 128-77°
	Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	37145 + 37146 SE1635-Z + SE1635-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10 22110 N120 Extension Ring 10 II	85204 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311 85204 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	Lens FOV Converted FOV107-63° 128-77° Lens FOV Converted FOV107-63° 128-77°
	Sony FE 24mm f/1.4 GM		¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 WACP - 2	Lens FOV Converted FOV84° 98°
	Sigma 14-24mm F2.8 DG DN	19726 SLE1424-Z	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21125 Extension Ring 25 with Lock	85204 WACP - 2	Lens FOV Converted FOV Zoom Range94-84° 115-98° 20-24mm
	Tamron 17-28mm f/2.8 Di III RXD	37157 STE1728-Z 37157 + 37158 STE1728-Z + STE1728-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 WACP - 2	Lens FOV Converted FOV104-75° 123-89°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.
* Recommended port system based on best optical performance

85204
0.57X WIDE ANGLE CONVERSION PORT WACP-2

Package includes :

- Hard Lens Cap
- Rear Port Cap
- Spare O-ring 90140
- Lubricant
- Cleaning Cloth
- Carrying Bag

Specification

Dimension (dia x length)	267 x 220 mm
Weight in Air	7.35 kg
Buoyancy in Water	0.27 kg
Body Construction	Hard-anodized aluminum alloy
Lens Construction	4 Elements in 4 Groups
Lens Coating	Anti-reflection Coating on both sides
Lens Mount	N120 Port Mount
Depth Rating	100m
Focal Distance	From front element of lens to infinity
Field of View (Underwater)	140° (ref 14mm equiv.)

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.
* Recommended port system based on best optical performance